

### DC Series

Deep Cycle series batteries are designed to have a large amount of stored current discharged between charging sessions, with very heavy non-porous battery plates to withstand repeated major discharging and charging cycle(deep cycle). The Deep-cycle batteries uses a different chemistry for the plates active paste material, and a slightly stronger electrolyte than normal battery electrolyte, which allows for a much longer life in deep cycle applications.

### DC12650

(12V65Ah/10hr)




### Application

- E-Bike
- Alarm System
- Cable Television
- Power tools
- Emergency Power System
- Security System
- Golf Cars
- Medical Equipment
- Solar and Wind Power System
- Communication Equipment
- Control Equipment
- Toys

### General Features

- Sealed and maintenance free operation.
- Non-Spillable construction design.
- ABS containers and covers optional.
- Safety valve installation for explosion proof .
- High quality and high reliability.
- Exceptional deep discharge recovery performance.
- Low self discharge characteristic.
- Flexibility design for multiple install positions.



### CONSTRUCTION

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Copper	Fiberglass	Sulfuric acid

### TECHNOLOGY PARAMETER

Battery model	DC12650			
Designed Cycle Life	> 350 Cycles @ -0.5CA to 9.6V			
Capacity (25 °C)	20hR(3.325A, 10.5V)	10hR(3.25A, 10.5V)	5hR(12.5A, 10.5V)	1hR(41.9A, 9.60V)
	66.5Ah	65.0Ah	60.25Ah	41.9Ah
Dimensions	Length	Width	Height	Total Height
	350 ±2mm	167 ±2mm	173 ±2mm	173 ±2mm
Approx. weight (±5%)	20.5Kg (45.53 lbs)			
Internal resistance	Full charged at 25 °C: Approx. 8.0mOhms			
Self discharge	3% of capacity declined per month at 25 °C (average)			
Capacity Affected by Temp.(20HR)	40 °C	25 °C	0 °C	-15 °C
	102%	100%	85%	65%
Charge Voltage (25 °C)	Cycle use		Float use	
	14.4-14.7V(-30mV/°C), max. Current:19.50A		13.5-13.8V(-20mV/°C)	

### DC12650(12V65Ah/10hr)

Constant current discharge ratings-amperes at 25°C

End Point Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60V	210	159	121	70.8	40.7	17.9	11.7	6.70	3.51
1.65V	200	152	115	69.5	39.2	17.3	11.4	6.65	3.47
1.70V	188	143	109	68.2	37.7	16.7	11.0	6.58	3.45
1.75V	176	135	103	66.9	36.2	16.0	10.7	6.53	3.40
1.80V	164	128	97.2	65.6	34.7	15.3	10.4	6.50	3.37

Constant power discharge ratings-watts at 25°C

End Point Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60V	378	287	220	130	74.9	33.1	21.7	12.5	6.60
1.65V	357	273	208	127	71.8	31.9	21.0	12.4	6.50
1.70V	334	256	196	123	68.6	30.6	20.3	12.2	6.42
1.75V	311	240	185	120	65.6	29.2	19.6	12.0	6.30
1.80V	289	226	173	117	62.5	27.7	18.9	11.7	6.20

